

Paver Clean PW Paver Wash Instructions

Veá la página 3 para Español (See page 3 for Spanish)



PW

Paver Clean™ PW is a general-purpose paver wash. It is a must-use product to prepare pavers for sealing. This multi-purpose wash can tackle polyhaze, efflorescence and ground-in dirt. PW can easily be applied to pavers, retaining walls, brick and masonry, and should be used after spot cleaning.

COVERAGE

Up to 200 sq. ft. per gallon. Coverage may vary depending on surface and application.

CLEAN-UP

Rinse off all equipment with clean water and let dry.

STORAGE

KEEP FROM FREEZING. Store container in a cool area with cap or lid firmly in place. Rinse off all equipment with clean water and let dry.

FEATURES

- Opens surface pores to accept sealer
- Restores original paver color
- Contains no muriatic acid or hydrochloric acid

USER TIPS

- Wait 60-90 days for new pavers to cure before applying PW.
- Wear eye protection and rubber gloves when applying PW.
- Prolonged contact of cleaner on metal or other surfaces may result in etching or damage.
- Saturate vegetation before and after application of PW.
- **NOT FOR USE ON:**
 - » Sealed surfaces, wetcast or natural stone

Paver Clean PW Paver Wash Instructions

Veá la página 4 para Español (See page 4 for Spanish)

EASY 4-STEP PROCESS

1

PREP



- Thoroughly sweep surface of joint sand, dust, debris or loose material.
- Spot clean if needed with one of these SRW Specialty Clean™ products:
CD = Cleaner & Degreaser
RE = Rust Eliminator
MC = Mold, Moss & Mildew Cleaner
OC = Organic Stain Cleaner
TR = Tar, Gum & Rubber Remover

2

WET



- Saturate surface & surrounding area (including vegetation) thoroughly with water.
- Do not allow product to dry on surface. Re-spray with water, if needed, to keep area wet. A 2-person application is recommended.

3

APPLY



- Apply PW directly to surface with a sprinkler can. Do not dilute.
- With a stiff bristle brush, scrub area immediately & thoroughly.
- For large areas, work in 200 sq. ft. sections.
- If working on an incline, start at the highest point, working in small sections. Scrub from bottom of section, pushing excess PW up over job.

4

RINSE



- Immediately rinse surface & surrounding areas (including vegetation) thoroughly with clean water until all traces of foam disappear.
- Repeat if necessary. Let dry.
- Wait at least 24 hours to apply SRW Paver Seal™ products.



WARNING: Contains Sulfamic Acid. Avoid contact to skin, eyes and clothing.

FIRST AID: Wash with warm soapy water if skin contact occurs. For any eye contact, flush immediately and thoroughly with clean water for 15 minutes and seek medical attention. Do not mix with any other materials/liquids except water.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.

VOC 0 g/L (0 lbs/gallon)

KEEP OUT OF THE REACH OF CHILDREN.

Manufactured in the USA for SRW Products, Princeton, MN 55371.