

# Premium Stone Clean SW Stone Wash Instructions

Vea la página 3 para Español (See page 3 for Spanish)



## SW

Premium Stone Clean™ SW is a concentrated general-purpose stone wash. It is a must-use product to prepare natural stone for sealing because it removes ground-in dirt, dust, light grease and oil from the surface which can interfere with proper sealer bonding. This wash should be used after spot treatments.

## COVERAGE

Up to 200 sq. ft. per gallon (18.58 sq. m. per 3.78 liters) when diluted. Coverage may vary depending on surface and application.

## CLEAN-UP

Rinse off all equipment with soap and water and let dry.

## STORAGE

KEEP FROM FREEZING. Store container in a cool area with cap or lid firmly in place.

## FEATURES

- Concentrated formula for natural stone surfaces
- Removes ground-in dirt, light grease and oil
- Non-acidic, easy to use formula

## APPLICATIONS

- Granite/Quartz
- Limestone
- Marble/Travertine
- Bluestone/Sandstone
- NOT FOR USE ON:
  - » Sealed surfaces

## USER TIPS

- Wear eye, skin and respiratory protection when applying.
- Always test a small, discrete area before use.
- Prolonged contact of cleaner on metal or other surface may result in etching or damage.
- Ask stone dealer about cleaning procedures for manufactured stone.

# Premium Stone Clean SW Stone Wash Instructions

Veá la página 4 para Español (See page 4 for Spanish)

## EASY 4-STEP PROCESS

1

PREP



- Thoroughly sweep surface of joint sand, dust, debris or loose material.
- Spot clean if needed with one of these SRW Specialty Clean™ products:  
**CD** = Cleaner & Degreaser  
**OC** = Organic Stain Cleaner  
**MC** = Mold, Moss & Mildew Cleaner

2

WET



- Dilute equal parts SW with warm clean water.
- Saturate surface & surrounding area (including vegetation) thoroughly with water.
- Do not allow product to dry on surface. Re-spray with water, if needed, to keep area wet. A 2-person application is recommended.

3

APPLY



- Apply mixture directly to surface with a sprinkler can.
- Scrub with a stiff bristle brush. Let sit for 5 minutes. Keep wet. Rescrub.
- For large areas, work in 200 sq. ft. (18.58 sq. m.) sections.
- If working on an incline, start at the highest point, working in small sections. Scrub from the bottom of the section, pushing excess SW up over job.

4

RINSE



- Immediately rinse surface & surrounding areas (including vegetation) thoroughly with clean water until all traces of cleaner are gone.
- Repeat if necessary. Let dry.
- Wait 24 hours to apply SRW Stone Seal™ products.

**WARNING: VAPOR HARMFUL.** Contains Sodium Metasilicate Pentahyd. May affect the brain or central nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. May cause allergic skin reaction. Harmful if swallowed. Use only with adequate ventilation. Avoid contact with eyes and skin.

**KEEP OUT OF THE REACH OF CHILDREN.**

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately. For skin, wash thoroughly with soap and water. If swallowed, DO NOT INDUCE VOMITING. Give conscious victim 1 to 2 glasses of water and get medical attention immediately.

**IMPORTANT NOTICE:** Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.

DOT Shipping name: UN1719, Caustic Alkali Liquids, N.O.S., (Disodium Trioxosilicate, Pentahydrate), 8, III

VOC 0 g/L (0 lbs/gallon)

Manufactured in the USA for SRW Products, Princeton, MN 55371

Reorder #STONE SW CTN